



### Outdoor units

DUCT


RAV-SM566BTP-E



RAV-SM806BTP-E



RAV-SM1106BTP-E  
RAV-SM1406BTP-E



## Cost Saving



## Comfort



## An efficient use of time



TOSHIBA

Notice : Toshiba is committed to continuously improving its products, to ensure the highest quality and reliability standards, and to meet local regulations and market requirements. All features and specifications subject to change without prior notice.



**TOSHIBA**  
Leading Innovation >>>



# Super Digital Inverter

Inverter Air Conditioning for Light Commercial Use



Made In Japan

Applicable to certain models.



## Super Digital Inverter

Toshiba Super Digital Inverter series air conditioners combine economy and ecology in a compact body. They feature state-of-the-art technology, flexible control, and easy installation to bring natural comfort and convenience to any business environment. A complete range of indoor units: Cassette, Ducted, Ceiling and High wall units.


### Superior EER

Very efficient energy consumption. Keeps down operating costs. EER of 4.52\* and COP of 4.79\* achieved by Toshiba's unrivalled Super Digital Inverter technologies and newly developed components.

\*4HP outdoor unit  
Internation model



### The industry's first magnetic-action control



The new structure allows a huge reduction in energy loss. The balanced magnetic-action force to rise and the rotor's weight minimized the friction laid on the axis provides excellent operation efficiency.

### ECO-driving DC twin rotary



#### R410A refrigerant

An ozone layer depletion coefficient of zero has become absolutely essential for an advanced air conditioning system.

#### Vector-controlled inverter

Vector IPDU control changes the motor current wave to a smooth sine pattern so that noise emitted from the drive units is greatly reduced.

#### High efficiency heat-transfer (flat fin)

Heat-transfer tube with improved heat-transfer coefficient.

#### DC fan motor

Highly Efficient DC Motor.

#### Bat wing fan


New development for high-pressure low-volume fan.

#### Wide-flow grille

Optimizing ventilation performance, bringing out the full effect of fan and motor.

#### DC twin rotary compressor

A low minimum speed of 10 rps has been achieved.



Note: Actual component may vary considerably from specifications depending on product model.

## Remote Controllers

Toshiba Digital Inverters operated with an easy-to-use remote controller.


	Indoor unit	4-Way Cassette RAV-SM**4UTP-E	Ducted RAV-SM**6BTP-E	Under Ceiling RAV-SM**7CTP-E	High-Wall RAV-SM**6KRT-E
Remoto controller <b>RBC-AX32U(W)-E</b> Wireless remote controller kit	*				
<b>RBC-AX32CE2</b> Wireless remote controller kit				*	
<b>TCB-AX32E2</b> Wireless remote controller kit			*		*
<b>RBC-AMS51E-EN</b> Lite-Vision plus remote controller	*	*	*	*	*
<b>RBC-AMT32E</b> Wired remote controller	*	*	*	*	*
<b>RBC-EXW21E</b> Weekly timer	*	*	*	*	*
<b>TCB-SC642TLE2</b> Central remote controller	*	*	*	*	*
<b>WH-L11SE</b> Wireless remote controller					*

Note: To link to CRC Control, a net adapter interface card is required - model TCB-PCNT30TLE2



## Operating temperature range


Heater operation is possible starting from an outdoor temperature of -20°C creates a comfortable space even during cold winters, while cooling operation is possible at -15°C outdoor temperature. This enables wider applications and use of the system in colder regions.



## Self-Clean operation-Continuing high performance for energy saving

This enables indoor unit type and Ceiling type to maintain energy efficiency at the time of purchase for a long time.  
The mechanism of the wash-off

1. The aqua resin coating prevents dirt from sticking to the fins.
2. The condensation water flows and washes away dirt.
3. After washing, a drying operation suppresses the propagation of mold.




## Quiet operation

Low-noise design. If the outdoor temperature is 30°C or less, operates at under 45dB(A). It's possible to automatically operate the quiet operation mode below 35°C air temperature.




## Frost protection

8°C operation for frost protection is possible for the combination with Super Digital Inverter.  
(4-Way and Slim Duct series 4)




## Sub cool path

Improve reliability for smooth drainage. The outdoor unit of Super Digital Inverter is equipped with "Sub cool path" preventing freeze under a heat exchanger. (Only 3HP to 6HP)




## Height Difference

Super Digital Inverter leads the industry with support for height differences of up to 30 meters on a single system. That is enough height to cover an 8-story building.



## Compatible with pipes up to 75 meters long

Enable the outdoor unit to be installed out of sight increases installation flexibility. (Only 4HP to 6HP)



### 1. combination

type		4way cassette				4way cassette (with twin kit)	
		SDI	SDI	SDI	SDI	SDI	SDI
system-type							
indoor-type		4way	4way	4way	4way	4way	4way
capacity	hp	2	3	4	5	2x2	3x2
indoor		<b>RAV-SP564UTP-E</b>	<b>RAV-SM804UTP-E</b>	<b>RAV-SM1104UTP-E</b>	<b>RAV-SM1404UTP-E</b>	<b>RAV-SM564UTP-E</b>	<b>RAV-SM804UTP-E</b>
Qty-indoor unit		1	1	1	1	2	2
outdoor		<b>RAV-SP564ATP-SG</b>	<b>RAV-SP804ATP-SG</b>	<b>RAV-SP1104AT-SG</b>	<b>RAV-SP1404AT-SG</b>	<b>RAV-SP1104AT-SG</b>	<b>RAV-SP1404AT-SG</b>
controller (wireless)		RBC-AX32U(W)-E					
cooling capacity-rated	kW	4.8	5.8	9.7	11.2	4.8	5.8
cooling capacity-range	kW	<1.2 - 5.6>	<1.9 - 8.0>	<2.6 - 11.0>	<2.6 - 14.0>	<1.2 - 5.6 >	<1.9 - 8.0 >
cooling power input-rated	kW	1.27	1.35	2.25	2.95	1.27	1.35
NEA tick	tick	√√√	√√√√	√√√√	√√√	√√√√	√√√
running current (230V)	A	5.6	6.2	12.53	16.8	5.6	6.2
flare connection main pipe (gas)	mm	12.7	15.9	15.9	15.9	12.7	15.9
flare connection main pipe (liquid)	mm	6.4	9.5	9.5	9.5	6.4	9.5
pipe length (min)	m	5	5	5	5	5	5
pipe length (max)	m	50	50	75	75	75	75
chargeless length	m	20	20	30	30	30	30
branch kit						RBC-TWP30E2	RBC-TWP50E2

### 2. indoors

model name		<b>RAV-SM564UTP-E</b>	<b>RAV-SM804UTP-E</b>	<b>RAV-SM1104UTP-E</b>	<b>RAV-SM1404UTP-E</b>	<b>RAV-SM564UTP-E × 2</b>	<b>RAV-SM804UTP-E × 2</b>
indoor		4way	4way	4way	4way	4way	4way
capacity	hp	2	3	4	5	2x2	3x2
air flow-H	m3/h	1,050	1,230	2,010	2,100	1,050	1,230
air flow-M	m3/h	870	960	1,440	1,440	870	960
air flow-L	m3/h	780	810	1,170	1,230	780	810
sound pressure level (L)/(M)/(H)	dB	28 / 29 / 32	28 / 31 / 35	33 / 38 / 43	34 / 38 / 44	28 / 29 / 32	28 / 31 / 35
dimension (H × W × D)	mm	256 × 840 × 840	256 × 840 × 840	319 × 840 × 840	319 × 840 × 840	256 × 840 × 840	256 × 840 × 840
weight	kg	20	20	24	24	20	20
panel model name		RBC-U31PG(W)-E	RBC-U31PG(W)-E	RBC-U31PG(W)-E	RBC-U31PG(W)-E	RBC-U31PG(W)-E	RBC-U31PG(W)-E
panel dimension (H × W × D)	mm	30 × 950 × 950	30 × 950 × 950	30 × 950 × 950	30 × 950 × 950	30 × 950 × 950	30 × 950 × 950
panel weight	kg	4.2	4.2	4.2	4.2	4.2	4.2
fan type		turbo fan	turbo fan	turbo fan	turbo fan	turbo fan	turbo fan
fan motor	W	14	20	68	72	14	20
air filler		Long life filter	Long life filter	Long life filter	Long life filter	Long life filter	Long life filter
attached remote controller (wireless)		RBC-AX32U(W)-E					
power input-max(for Name Plate)	W	40	40	120	120	40	40

### 3. outdoor

model name		<b>RAV-SP564ATP-SG</b>	<b>RAV-SP804ATP-SG</b>	<b>RAV-SP1104AT-SG</b>	<b>RAV-SP1404AT-SG</b>	<b>RAV-SP1104AT-SG</b>	<b>RAV-SP1404AT-SG</b>
outdoor-type		DI	DI	DI	DI	DI	DI
capacity	hp	2	3	4	5	4	5
phase		1	1	1	1	1	1
power supply	V	230	230	230	230	230	230
power supply (Hz)	Hz	50	50	50	50	50	50
air-flow	m3/hr	2,400	3,000	6,060	6,180	6,060	6,180
sound pressure level	dB	48	49	50	52	50	52
dimension (H × W × D)	mm	550 × 780 × 290	890 × 900 × 320	1340 × 900 × 320	1340 × 900 × 320	1340 × 900 × 320	1340 × 900 × 320
weight	kg	44	66	93	93	93	93
compressor type		DC Twin Rotary					
fan motor output	w	43	43	100	100	100	100
Refrigerant Quantity in Outdoorunit	kg	1.4	2.1	3.1	3.1	3.1	3.1
Additional refrigerant charge	g/m	20	40	40	40	40	40
power input-max(for NamePlate)	kw	3.19	4.84	4.87	4.87	4.87	4.87
installation fuse rating	A	16	25	25	25	25	25
power wire	mm2	1.5	2.5	2.5	2.5	2.5	2.5
indoor/outdoor connecting wire	mm2	1.5	1.5	1.5	1.5	1.5	1.5

### 1. combination

type		Hi Wall		Hi Wall (with Twin Kit)	
system-type		SDI	SDI	SDI	SDI
indoor-type		high wall	high wall	high wall	high wall
capacity	hp	2	3	2x2	3x2
indoor		<b>RAV-SM566KRT-E</b>	<b>RAV-SM806KRT-E</b>	<b>RAV-SM566KRT-E</b>	<b>RAV-SM806KRT-E</b>
Qty-indoor unit		1	1	2	2
outdoor		<b>RAV-SP564ATP-SG1</b>	<b>RAV-SP804ATP-SG1</b>	<b>RAV-SP1104AT-SG1</b>	<b>RAV-SP1404AT-SG1</b>
cooling capacity-rated	kW	4.8	6.8	4.8	6.8
cooling capacity-range	kW	< 1.2 - 5.6 >	< 1.9 - 8.0 >	< 1.2 - 5.6 >	< 1.9 - 8.0 >
cooling power input-rated	kW	1.43	2.01	1.43	2.01
NEA tick	tick	√/√	√/√	√/√/√	√/√
running current (230V)	A	6.36	9.15	6.36	9.15
flare connection main pipe (gas)	mm	12.7	15.9	12.7	15.9
flare connection main pipe (liquid)	mm	6.4	9.5	6.4	9.5
pipe length (min)	m	5	5	5	5
pipe length (max)	m	50	50	75	75
chargeless length	m	20	20	30	30
branch kit				RBC-TWP30E2	RBC-TWP50E2

### 2. indoors

model name		<b>RAV-SM566KRT-E</b>	<b>RAV-SM806KRT-E</b>	<b>RAV-SM566KRT-E × 2</b>	<b>RAV-SM806KRT-E × 2</b>
indoor-type		high wall	high wall	high wall	high wall
capacity	hp	2	3	2x2	3x2
air flow-H	m³/h	840	1,020	840	1,020
air flow-M	m³/h	750	750	750	750
air flow-L	m³/h	660	660	660	660
sound pressure level (L) / (M) / (H)	dB	36 / 39 / 42	36 / 41 / 47	36 / 39 / 42	36 / 41 / 47
dimension (H × W × D)	mm	320 × 1050 × 228	320 × 1050 × 228	320 × 1050 × 228	320 × 1050 × 228
weight	kg	12	12	12	12
fan type		cross flow fan	cross flow fan	cross flow fan	cross flow fan
fan motor output	W	30	30	30	30
air filter		Attached	Attached	Attached	Attached
attached remote controller (wireless)		WH-L11SE	WH-L11SE	WH-L11SE	WH-L11SE
power input-max(for NamePlate)	W	50	70	50	70

### 3. outdoors

model name		<b>RAV-SP564ATP-SG1</b>	<b>RAV-SP804ATP-SG1</b>	<b>RAV-SP1104AT-SG1</b>	<b>RAV-SP1404AT-SG1</b>
outdoor-type		SDI	SDI	SDI	SDI
capacity	hp	2	3	4	5
phase	1	1	1	1	1
power supply	v	230	230	230	230
power supply (Hz)	Hz	50	50	50	50
air flow	m³/h	2,400	3,000	6,060	6,180
sound pressure level	dB	48	49	50	52
dimension (H × W × D)	mm	550 × 780 × 290	890 × 900 × 320	1340 × 900 × 320	1340 × 900 × 320
weight	kg	44	66	93	93
compressor type		DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary
fan motor output	W	43	43	100	100
Refrigerant Quantity in Outdoorunit	kg	1.4	2.1	3.1	3.1
Additional refrigerant charge	g/m	20	40	40	40
power input-max(for NamePlate)	kw	3.19	4.84	4.87	4.87
installation fuse rating	A	16	25	25	25
power wire	mm²	1.5	2.5	2.5	2.5
indoor/outdoor connecting wire	mm²	1.5	1.5	1.5	1.5

### 1. combination

type		Standard ducted				Standard ducted (with Twin Kit)	
		SDI	SDI	SDI	SDI	SDI	SDI
system-type							
indoor-type		duct	duct	duct	duct	duct	duct
capacity rank	hp	2	3	4	5	2x2	3x2
indoor		<b>RAV-SM566BTP-E</b>	<b>RAV-SM806BTP-E</b>	<b>RAV-SM1106BTP-E</b>	<b>RAV-SM1406BTP-E</b>	<b>RAV-SM566BTP-E</b>	<b>RAV-SM806BTP-E</b>
Qty-indoor unit		1	1	1	1	2	2
outdoor		<b>RAV-SP564ATP-SG1</b>	<b>RAV-SP8034ATP-SG1</b>	<b>RAV-SP1104AT-SG1</b>	<b>RAV-SP1404AT-SG1</b>	<b>RAV-SP1104AT-SG1</b>	<b>RAV-SP1404AT-SG1</b>
controller (wired)		RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E
cooling capacity-rated	kW	5.0	7.1	10.0	12.5	5.0	7.1
cooling capacity-range	kW	< 1.2 - 5.6 >	< 1.9 - 8.0 >	< 2.6 - 12.0 >	< 2.6 - 14.0 >	< 1.2 - 5.6 >	< 1.9 - 8.0 >
cooling power input-rated	kW	1.4	2.1	2.64	3.74	1.49	2.1
running current (230V)	A	6.54	9.45	11.7	16.6	6.54	9.45
flare connection main pipe (gas)	mm	12.7	15.9	15.9	15.9	12.7	15.9
flare connection main pipe (liquid)	mm	6.4	9.5	9.5	9.5	6.4	9.5
pipe length (min)	m	5	5	5	5	5	5
pipe length (max)	m	50	50	75	75	75	75
chargeless length	m	20	20	30	30	30	30
branch kit						RBC-TWP30E2	RBC-TWP50E2

### 2. indoors

model name		<b>RAV-SM566BTP-E</b>	<b>RAV-SM806BTP-E</b>	<b>RAV-SM1106BTP-E</b>	<b>RAV-SM1406BTP-E</b>	<b>RAV-SM566BTP-E × 2</b>	<b>RAV-SM806BTP-E × 2</b>
indoor-type		duct	duct	duct	duct	duct	duct
capacity	hp	2	3	4	5	2x2	3x2
air flow-H	m³/h	800	1,200	2,100	2,100	800	1200
air flow-M	m³/h	630	930	1,650	1,650	630	930
air flow-L	m³/h	480	720	1,260	1,260	480	720
sound pressure level (L)/(M)/(H)	dB	25 / 29 / 33	26 / 30 / 34	33 / 36 / 40	33 / 36 / 40	25 / 29 / 33	26 / 30 / 34
dimmension (H × W × D)	mm	275 × 700 × 750	275 × 1000 × 750	275 × 1400 × 750	275 × 1400 × 750	275 × 700 × 750	275 × 1000 × 750
weight	kg	23	30	40	40	23	30
external static pressure (std)	Pa	40	40	40	40	40	40
external static pressure (upper)	Pa	120	120	120	120	120	120
external static pressure (lower)	Pa	30	30	30	30	30	30
fan type		centrifugal fan	centrifugal fan	centrifugal fan	centrifugal fan	centrifugal fan	centrifugal fan
fan motor output		120	120	120	120	120	120
air filter		Long life filter	Long life filter	Long life filter	Long life filter	Long life filter	Long life filter
attached remote controller (wired)		RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E
power input-max(for NamePlate)	w	150	150	250	250	150	150

### 3. outdoors

model name		<b>RAV-SP564ATP-SG</b>	<b>RAV-SP804ATP-SG</b>	<b>RAV-SP1104AT-SG</b>	<b>RAV-SP1404AT-SG</b>	<b>RAV-SP1104AT-SG</b>	<b>RAV-SP1404AT-SG</b>
outdoor-type		SDI	SDI	SDI	SDI	SDI	SDI
capacity rank	hp	2.0	3.0	4.0	4.0	5.0	5.0
phase		1	1	1	1	1	1
power supply	v	230	230	230	230	230	230
power supply (Hz)	Hz	50	50	50	50	50	50
air flow	m³/h	2,400	3,000	6,060	6,180	6,060	6,180
sound pressure level (cooling)	dB	48	49	50	52	50	52
dimension (H × W × D)	mm	550 × 780 × 290	890 × 900 × 320	1340 × 900 × 320	1340 × 900 × 320	1340 × 900 × 320	1340 × 900 × 320
weight	kg	44	66	93	93	93	93
compressor type		DC Twin Rotary					
fan motor output	w	43	43	100	100	100	100
Refrigerant Quantity in Outdoor unit	kg	1.4	2.1	3.1	3.1	3.1	3.1
Additional refrigerant charge	g/m	20	40	40	40	40	40
power input-max(for NamePlate)	kw	3.19	4.84	4.87	4.87	4.87	4.87
installation fuse rating	A	16	25	25	25	25	25
power wire	mm²	1.5	2.5	2.5	2.5	2.5	2.5
indoor/outdoor connecting wire	mm²	1.5	1.5	1.5	1.5	1.5	1.5

## 1. combination

type		Under ceiling				Under ceiling (with Twin Kit)	
		SDI	SDI	SDI	SDI	SDI	SDI
system-type							
indoor-type		ceiling	ceiling	ceiling	ceiling	ceiling	ceiling
capacity	hp	2	3	4	5	2x2	3x2
indoor		<b>RAV-SM568CTP-E</b>	<b>RAV-SM808CTP-E</b>	<b>RAV-SM1108CTP-E</b>	<b>RAV-SM1408CTP-E</b>	<b>RAV-SM568CTP-E</b>	<b>RAV-SM808CTP-E</b>
Qty-indoor unit		1	1	1	1	2	2
outdoor		<b>RAV-SP564TP-SG1</b>	<b>RAV-SP804ATP-SG1</b>	<b>RAV-SP1104AT-SG1</b>	<b>RAV-SP1404AT-SG1</b>	<b>RAV-SP1104AT-SG1</b>	<b>RAV-SP1404AT-SG1</b>
controller (wired)		RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E
cooling capacity-rated	kW	5.0	7.1	10.0	12.5	5.0	7.1
cooling capacity-range		< 1.2 - 5.6 >	< 1.9 - 8.0 >	< 2.6 - 12.0 >	< 2.6 - 14.0 >	< 1.5 - 5.6 >	< 1.5 - 8.0 >
cooling power input-rated	kW	1.42	1.72	2.74	3.74	1.42	2.1
NEA tick	tick	√/√	√/√	√/√/√	√/√	√/√/√	√/√
running current (230V)	A	6.54	9.38	11.0	16.6	6.36	9.38
flare connection main pipe (gas)	mm	12.7	15.9	15.9	15.9	12.7	15.9
flare connection main pipe (liquid)	mm	6.4	9.5	9.5	9.5	6.4	9.5
pipe length (min)	m	5	5	5	5	5	5
pipe length (max)	m	50	50	75	75	75	75
chargeless length	m	20	20	30	30	30	30
branch kit						RBC-TWP30E2	RBC-TWP50E2

## 2. indoors

model name		<b>RAV-SM568CTP-E</b>	<b>RAV-SM808CTP-E</b>	<b>RAV-SM1108CTP-E</b>	<b>RAV-SM1408CTP-E</b>	<b>RAV-SM568CTP-E × 2</b>	<b>RAV-SM808CTP-E × 2</b>
indoor-type		ceiling	ceiling	ceiling	ceiling	ceiling	ceiling
capacity rank	hp	2	3	4	5	2x2	3x2
air flow-H	m³/h	900	1,410	1,860	2,040	900	1,410
air flow-M	m³/h	720	1,002	1,350	1,530	720	1,002
air flow-L	m³/h	540	750	1,020	1,200	540	750
air-flow-H	m³/min	15.0	23.5	31.0	34.0	15.0	23.5
air-flow-M	m³/min	12.0	16.7	22.5	25.5	12.0	16.7
air-flow-L	m³/min	9.0	12.5	17.0	20.0	9.0	12.5
sound pressure level (L)/(M)/(H)	dB	28/35/37	29/36/41	32/38/44	35/41/46	28 / 35 / 37	29 / 36 / 41
dimmension (H × W × D)	mm	235 × 950 × 690	235 × 1,270 × 690	235 × 1,586 × 690	235 × 1,586 × 690	235 × 950 × 690	235 × 1,270 × 690
weight	kg	23	29	35	35	23	29
fan type		centrifugal fan	centrifugal fan	centrifugal fan	centrifugal fan	centrifugal fan	centrifugal fan
fan motor output		94	94	139	139	94	94
air filter		Long life filter	Long life filter	Long life filter	Long life filter	Long life filter	Long life filter
attached remote controller (wired)		RBC-AMT32-E	RBC-AMT32-E	RBC-AMT32-E	RBC-AMT32-E	BBC-AMT32-E	BBC-AMT32-E
power input-max(for NamePlate)	W	94	94	150	150	94	94

## 3. outdoors

model name		<b>RAV-SP564ATP-SG1</b>	<b>RAV-SP804ATP-SG1</b>	<b>RAV-SP1104AT-SG1</b>	<b>RAV-SP1404AT-SG1</b>	<b>RAV-SP1104AT-SG1</b>	<b>RAV-SP1404AT-SG1</b>
outdoor-type		SDI	SDI	SDI	SDI	SDI	SDI
capacity rank		2	3	4	5	4	5
phase		1	1	1	1	1	1
power supply	v	230	230	230	230	230	230
power supply	(Hz)	50	50	50	50	50	50
air flow	m³/h	2,400	2,700	4,500	4,500	4,500	4,500
sound pressure level (cooling)	dB	48	49	50	52	50	52
dimension (H × W × D)	mm	550 × 780 × 290	890 × 900 × 320	1340 × 900 × 320	1340 × 900 × 320	1340 × 900 × 320	1340 × 900 × 320
weight	kg	44	66	93	93	93	93
compressor type		DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Rotary	DC Twin Ratory	DC Twin Ratory
fan motor output	w	43	43	100	100	100	100
Refrigerant Quantity in Outdoor unit	kg	1.4	2.1	3.1	3.1	3.1	3.1
Additional refrigerant charge	g/m	20	40	40	40	40	40
power wire	mm²	1.5	2.5	2.5	2.5	2.5	2.5
indoor/outdoor connecting wire	mm²	1.5	1.5	1.5	1.5	1.5	1.5

### 1. combination

type		Standard ducted (hi eff)				Standard ducted (with Twin Kit)	
system-type		SDI	SDI	SDI	SDI	SDI	SDI
indoor-type		duct	duct	duct	duct	duct	duct
capacity rank	hp	2	3	4	5	2x2	3x2
indoor		<b>RAV-SM566BTP-E</b>	<b>RAV-SM806BTP-E</b>	<b>RAV-SM1106BTP-E</b>	<b>RAV-SM1406BTP-E</b>	<b>RAV-SM566BTP-E</b>	<b>RAV-SM806BTP-E</b>
Qty-indoor unit		1	1	1	1	2	2
outdoor		<b>RAV-SP564ATP-SG1</b>	<b>RAV-SP804ATP-SG1</b>	<b>RAV-SP1104AT-SG1</b>	<b>RAV-SP1404AT-SG1</b>	<b>RAV-SP1104AT-SG1</b>	<b>RAV-SP1404AT-SG1</b>
controller (wired)		RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E
cooling capacity-rated	kW	4.8	5.8	9.7	11.2	4.8	6.1
cooling capacity-range	kW	< 1.2 - 5.6 >	< 1.9 - 8.0 >	< 2.6 - 11.0 >	< 2.6 - 14.0 >	< 1.2 - 5.6 >	< 1.9 - 8.0 >
cooling power input-rated	kW	1.42	1.72	2.74	3.74	1.42	1.72
running current (230V)	A	6.54	8.14	12.53	16.8	6.54	8.14
flare connection main pipe (gas)	mm	12.7	15.9	15.9	15.9	12.7	15.9
flare connection main pipe (liquid)	mm	6.4	9.5	9.5	9.5	6.4	9.5
pipe length (min)	m	5	5	5	5	5	5
pipe length (max)	m	50	50	75	75	75	75
chargeless length	m	20	20	30	30	30	30
branch kit						RBC-TWP30E2	RBC-TWP50E2

### 2. indoors

model name		<b>RAV-SM566BTP-E</b>	<b>RAV-SM806BTP-E</b>	<b>RAV-SM1106BTP-E</b>	<b>RAV-SM1406BTP-E</b>	<b>RAV-SM566BTP-E x 2</b>	<b>RAV-SM806BTP-E x 2</b>
indoor-type		duct	duct	duct	duct	duct	duct
capacity	hp	2	3	4	5	2x2	3x2
air flow-H	m³/h	800	1,200	2,100	2,100	800	1200
air flow-M	m³/h	630	930	1,650	1,650	630	930
air flow-L	m³/h	480	720	1,260	1,260	480	720
sound pressure level (L)/(M)/(H)	dB	25 / 29 / 33	26 / 30 / 34	33 / 36 / 40	33 / 36 / 40	25 / 29 / 33	26 / 30 / 34
dimmension (H x W x D)	mm	275 x 700 x 750	275 x 1000 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 700 x 750	275 x 1000 x 750
weight	kg	23	30	40	40	40	40
external static pressure (std)	Pa	40	40	40	40	40	40
external static pressure (upper)	Pa	120	120	120	120	120	120
external static pressure (lower)	Pa	30	30	30	30	30	30
fan type		centrifugal fan	centrifugal fan	centrifugal fan	centrifugal fan	centrifugal fan	centrifugal fan
fan motor output		120	120	120	120	120	120
air filter		Long life filter	Long life filter	Long life filter	Long life filter	Long life filter	Long life filter
attached remote controller (wired)		RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E
power input-max(for NamePlate)	w	150	150	250	250	150	150


### 3. outdoors

model name		<b>RAV-SP564ATP-SG</b>	<b>RAV-SP804ATP-SG</b>	<b>RAV-SP1104AT-SG</b>	<b>RAV-SP1404AT-SG</b>	<b>RAV-SP1104AT-SG</b>	<b>RAV-SP1404AT-SG</b>
outdoor-type		DI	DI	DI	DI	DI	DI
capacity rank	hp	2.0	3.0	4.0	4.0	5.0	5.0
phase		1	1	1	1	1	1
power supply	v	230	230	230	230	230	230
power supply (Hz)	Hz	50	50	50	50	50	50
air flow	m³/h	2,400	2,700	4,500	4,500	4,500	4,500
sound pressure level (cooling)	dB	48	49	50	52	50	52
dimension (H x W x D)	mm	550 x 780 x 290	890 x 900 x 320	1340 x 900 x 320	1340 x 900 x 320	1340 x 900 x 320	1340 x 900 x 320
weight	kg	44	66	93	93	93	93
compressor type		DC Twin Rotary					
fan motor output	w	43	43	100	100	100	100
Refrigerant Quantity in Outdoor unit	kg	1.4	2.1	3.1	3.1	3.1	3.1
Additional refrigerant charge	g/m	20	40	40	40	40	40
power input-max(for NamePlate)	kw	3.19	4.84	4.87	4.87	4.87	4.87
installation fuse rating	A	16	25	25	25	25	25
power wire	mm²	1.5	2.5	2.5	2.5	2.5	2.5
indoor/outdoor connecting wire	mm²	1.5	1.5	1.5	1.5	1.5	1.5


**TOSHIBA**

Leading Innovation >>>

## SDI Super Digital Inverter 2HP : Outdoor unit drawings




## SDI Super Digital Inverter 3HP : Outdoor unit drawings



(Unit: mm)


## SDI Super Digital Inverter 4&5HP : Outdoor unit drawings




## Indoor units

Unit: mm


### 4-way cassette



### Ceiling



### HIGHWALL RAV-SM566KRT-E



### RAV-SM806KRT-E

